




WASHI PAPER MASKING TAPES

Riewoldt is specialized in the **converting** and **distribution** of high-performance materials for the adhesive tapes industry. We offer a wide range of **paper masking tapes** to address **masking** applications.



► WHY US ?



Certified quality



Global footprint



Custom solutions



Added value services



Sustainability

► OUR APPLICATIONS

A **washi paper masking tape** is made using Japanese natural local fibers. It is a **highly performing fine line masking tape, perfect for masking different kinds of surfaces**, from most to least delicate, guaranteeing the **best professional finishing** in terms of paint edges preventing paint from bleeding through and without annoying re-works, touch ups or surface damages.

These masking tapes are very thin, supple and at the same time **extremely tear-resistant and stable**. It unrolls well, can be easily removed **without leaving any residue, is UV-resistant and can withstand high temperatures**.



For high-quality painting and lacquering work



For ingrain wallpapers & sensitive surfaces




For scraped plaster, stucco and plaster work

► OUR CONVERTING CAPABILITIES



Unwinding & rewinding



Slitting



On roll slitting

We are able to convert the washi tapes according to your needs and if required, we can also brand the roll core with your name.

For further information please contact:

Riewoldt GmbH

Niederkasseler Str. 17, 51147 Köln

Tel: +49 (0)2203 60098-0

E-Mail: info@riewoldt.de

Internet: www.riewoldt.de



riwo

WASHI PAPER MASKING TAPE



YELLOW

ORANGE

LILA

PINK

GENERAL INFORMATION

Article description

This masking tape consist out of an impregnated, flat rice paper coated a UV resistant acrylic adhesive.

Low adhesion tape consisting of supple, extra thin special paper. It is made of an impregnated, tensile, adhesive rice paper, which is one side fully covered with acrylic adhesive.

This masking tape is made of an impregnated, high tensile, adhesive rice paper, which is one side fully covered with a special acrylic adhesive. Very stable and tear-resistant due to reinforced fibers.

Areas of application

Different types of substrates; excellent tack and adhesion to glass, aluminium, PVC, and many more. Also for sensible UV areas. Ensures sharp, clean and flat paint lines, ideal for high-quality painting and lacquering work.

Ingrain wallpapers & sensitive surfaces (Slightly adhesive). Suitable for fresh painted or fully cured painted.

Different types of surfaces; particularly suitable for scraped plaster, stucco and plaster work. For sensitive UV-areas & light humidity surfaces.

No leaks of paints and varnish.

Inside



Outside



Sensitive surfaces



PVC



Finished wood



Finery, Stone Concrete



Not applicable on

Wet and humid surfaces

Wet and humid surfaces

Wet surfaces

PRODUCT CHARACTERISTICS

Roll length

50m and other lengths on request

Roll width

19mm, 25mm, 30mm, 38mm and 50mm and other widths on request

Package quantity

48 rolls, 36 rolls, 32 rolls, 24 rolls, 24 rolls

Type of adhesion

Acrylic mid tack

Acrylic low tack

Acrylic high tack

Color

Yellow

Orange

Violet

Pink / Red

Roll core

3 inches

TECHNICAL DATA

Thickness

0,09mm

0,075mm

0,096mm

Adhesion on steel

1,40 N/10mm ±10%

0,75 N/10mm ±10%

1,5 N/10mm ±10%

Elongation at break

7,5% ±10%

5% ±10%

9% ±10%

Tensile strength

34 N/10mm ±10%

41 N/10mm ±10%

36 N/10mm ±10%

Optimal storage

Minimum +10°C, best at room temperature

T° resistance

120°C. (short-term)

Up to 100°C.

Up to 110 °C. (up to 60 min)

UV resistance

Up to 6 months

Up to 2 months

Up to 6 months

●●● Excellent suitability ●● Good suitability ● Suitable

For further information please contact:

Riewoldt GmbH

Niederkasseler Str. 17, 51147 Köln

Tel: +49 (0)2203 60098-0

E-Mail :info@riewoldt.de

www.riewoldt.de

RIEWOLDT
BONDING • SLITTING • DIE-CUTTING

Member of **ADDEV**
MATERIALS